

Technical Information

CeTePox 134 R

Characteristics Specially modified, medium-viscous epoxy resin with low crystallisation tendency

Properties and Fields of Application *CeTePox* 134 R is a universal epoxy resin binder which is preferably used for solvent free coating systems. It is especially used as a base for self levelling pigmented floor coatings with optimum surface properties.

	<i>Property</i>	<i>Value</i>	<i>Method of Determination</i>
Specification	Viscosity at 23 °C	64 – 90 s appr. 3,600 mPas	DIN 53 211, 8 mm DIN 53 015
	Density at 23 °C	appr. 1.14 g/cm ³	DIN 53 217, T 3
	Epoxide Value	appr. 0.49 eq./100 g	calculated
	Epoxy Equiv. Weight	204 g/eq.	CTP-TS 33/34-00

Storage At room temperature in originally packed units the shelf life is at least 12 months.

Remarks with Regard to Occupational Safety When working with epoxy resins and hardeners, the regulations of the "Berufsgenossenschaft der Chemischen Industrie" have to be considered (e.g. data sheet M 023 polyester and epoxy resins). Classification according EC-legislation: Xi "irritant".

The indications given in this technical information are based on thoroughly executed tests and are to give reference to the user. However, they are non-binding as we cannot take over any responsibility, also related to possible protective rights of third parties, due to the variety of treatment and applications.

TI 134R / E 11-01 / V 04